



## LATTYGOLD 92 JOINING SHEET

### Description:

Calendered sheets made of mineral and carefully selected synthetic fibres bonded with an acrylonitrile elastomer mix.

Anti-stick treatment on both faces.

Homologation: BAM (oxygen), DVGW (gas), KTW (drinking water), LNE (food processing industry), WRC (drinking water).

### Applications:

General use: chemistry and petrochemistry, energy.

It would be preferable to use the Lattycarb 96 seals for high-temperature steam applications and the Acid Lattygold 5 for highly corrosive fluids.

Temperature parameters, pressure and maximum speed in no way can be associated.

### Parameters:

T < 440°C

P < 10MPa (100 bar)

|                 | Size          | Per sheet (€ Excl. tax) |
|-----------------|---------------|-------------------------|
| <b>Thk. 0.5</b> | 1,500 x 1,000 | 76.40                   |
| <b>1</b>        | 1,500 x 1,000 | 107.66                  |
| <b>1.5</b>      | 1,500 x 1,000 | 158.60                  |
| <b>2</b>        | 1,500 x 1,000 | 200.27                  |
| <b>3</b>        | 1,500 x 1,000 | 299.83                  |
| <b>4</b>        | 1,500 x 1,000 | 439.90                  |

### CARRIAGE COSTS



**CARRIAGE COSTS ARE CALCULATED  
ACCORDING TO THE DELIVERY POINT**