



## 5910 LOCTITE QUICK GASKET

### Technical data sheet

Loctite Quick Gasket for instantaneous, reliable and long-life seals. It replaces precut gaskets of all sizes and shapes: up to 10 oil sump gaskets (on medium engines) in a cartridge.

#### Characteristics

- Stands all automobile fluids (oil, coolant)
- High thermal resistance; up to +200°C
- Replaces cut gaskets, whatever their sizes and shapes may be
- Low volatility

#### Key applications

- seals for cylinder head covers, oil pumps
- Calorstat boxes, oil/water pumps
- Distribution, transmission or oil pumps
- Gearboxes, crankshaft plates

#### Instructions for use

- Dry clean parts
- Remove the locking lug, turn the duct 90° anticlockwise and remove the cap
- Apply a 3-6 mm gasket on one of the surfaces by surrounding the assembly holes
- Put the 2 parts together within 15 minutes and tighten the bolts at the required level
- The part is once again functional; the surplus must be removed.
- After use, leave a 5 mm length of the product outside the duct, this hardens and forms a natural cap/protective coating

**Maximum use temperature:** +200°C

**Tariff** : 22.30 €(Excluding tax) 200ml

**CARRIAGE COSTS ARE CALCULATED  
ACCORDING TO THE DELIVERY POINT**

RUBBERS

POLYURETHANES

FOAMS

PLASTICS

10 rue Ferdinand

42000 SAINT-ETIENNE

FRANCE

 : [contact@devistechnique.com](mailto:contact@devistechnique.com)