



Washing hoses

SE666THR rubber hose

Fields of use:

Forcing back cold or hot water: in the agricultural/industrial environment, civil engineering works, etc...

Description:

- Tube : black smooth EPDM
- Frame : braid or synthetic textile lap
- Covering : black EPDM, 6 yellow strips, smooth surface

Technical data sheet:

- Great resistance to ageing factors, cold, heat, etc...
- Sturdy, flexible
- Stands acids and light fertilizers
- Use temperature :
 - Nonstop : -40°C +100°C
 - Point temperature : 120°C
- Sprinkler Pressure : 10 Bar
 - at 100°C : 6 Bar
- Complies with the following standards :
 - NFT47253 Type 1
 - NFT47251

Dimensions:

Internal diameter (mm)	Outside diameter (mm)	Weight (g/m)
12	18	213
15	21	274
19	26	386
25	33	551
30	39	722
34	43	779

This information is given as a rough guide and must be approved by you according to the parameters you apply (temperature, product concentration, pressure...)

SOLUTIONS ELASTOMERES disclaims all responsibility for these tests.

RUBBERS

POLYURETHANES

FOAMS

PLASTICS

10 rue Ferdinand

42000 SAINT-ETIENNE

France

✉ : contact@devistechnique.com