



Washing hoses

PVC nylon braided hose

Characteristics:

- Flexible and multipurpose hose that meets food quality standards, made up of a high-tenacity PVC textile braid
- Temperature use: -15° up to + 60°C
- Sprinkler pressure at 23°C
- Non-burst pressure at 23°C

Use:

- Transition of food liquids or products according to the simulating A, B and C except for alcohol solutions
- Supply of machines and compressed air tools
- Transition of industrial gas
- Transition of chemical products
- Forcing back of water
- It is strictly forbidden to use hydrocarbons and by-products
- It is strictly forbidden to carry fat products (vegetal oils, milk)

Size:

Internal Ø x outside Ø (mm)	Weight (g/m)	Curve Ø (mm)	Sprinkler pressure (bar)	Non_burst pressure (bar)
4 x 10 ± 0.2	86	40	20	60
6 x 12 ± 0.2	110	55	20	60
8 x 14 ± 0.5	130	60	20	60
10 x 16 ± 0.5	155	75	20	60
12 x 19 ± 0.5	216	80	20	60
13 x 20 ± 0.5	225	90	20	60
16 x 24 ± 0.5	319	110	20	60
19 x 27 ± 0.5	363	125	20	60
25 x 34 ± 0.8	524	150	15	50
38 x 48 ± 1.0	865	220	10	32
40 x 52 ± 1.0	1,036	280	10	25
50 x 64 ± 1.0	1,440	420	8	25

This information is given as a rough guide and must be approved by you according to the parameters you apply (temperature, product concentration, pressure...)

SOLUTIONS ELASTOMERES disclaims all responsibility for these tests.